

Elcometer 116 Whirling & Sling Hygrometer



Elcometer 116 Whirling & Sling Hygrometer

Can be used in accordance with:	
ASTM E 337-B	BS 2842

Elcometer 116 Whirling & Sling Hygrometer

The Elcometer 116A Whirling Hygrometer is available in °C scale.

A guide for Relative Humidity (RH) Calculation is supplied with each instrument. The dewpoint can be accurately obtained using Elcometer 114 Dewpoint Calculator.


The Elcometer 116C Bacharach Sling Hygrometer is a convenient, self contained instrument with a built in slide rule for the calculation of %RH and dewpoint. It has spirit filled thermometers and is also available in °C or °F scales.

- Lightweight and compact
- Manual operation no power supply required.
- Measuring range: -5 to 50°C (30 to 110°F)
- RH Accuracy: ±5% RH

Climatic Condition Testing
During the application of a
coating, the presence of
moisture in the environment,
or on the work surface, often
results in a poor quality finish.
Problems such as poor
adhesion of the coating or
premature corrosion of the
substrate can occur.

To determine the likelihood of moisture affecting the quality of the finish, it is essential that the surface temperature, air temperature, relative humidity (RH) and dewpoint are all measured.

Elcometer 114 Dewpoint Calculator



Elcometer 114 Dewpoint Calculator

At a glance

- Simple, low cost gauges used to determine the relative humidity & dewpoint.
- Lightweight and portable.

Elcometer 114 Dewpoint Calculator

This provides accurate values of Relative Humidity (RH) and Dewpoint from the wet and dry bulb temperatures measured by a Whirling or Sling Hygrometer - such as the Elcometer 116 range.

The range of the Elcometer 114 is -10°C to 50°C (14°F to 122°F) and it has an accuracy of ±1% of standard tables.

The calculator includes a °C to °F converter.

Model	Description	Part Number
Elcometer 116A	Whirling Hygrometer - Metric °C	G116A1
Elcometer 116C	ometer 116C Bacharach Sling Hygrometer - Metric °C	G116C1
	Bacharach Sling Hygrometer - Imperial °F	G116C2
Elcometer 114	Elcometer 114 Dewpoint Calculator	G1142

data sheet

Related products



Elcometer 319



Elcometer 6700

130

Elcometer 212



Elcometer 214L

The Elcometer 319 dewmeter has been designed to incorporate all the needs required for climate condition monitoring, in a single gauge. This simple to use dewcheck measures all the parameters required to determine if the climatic conditions are correct for coating to commence - including - air temperature, relative humidity, surface temperature, dewpoint temperature and deltaT - the difference between dewpoint and surface temperature.

A portable laboratory instrument which charts the ambient temperature and relative humidity using the hair method.

Designed to cope with routine day to day use, the Elcometer 212 digital pocket thermometer is the gauge to take fast, accurate measurements of either the surface or the coating temperature. The probe can be protected by folding it into the handle - this also switches the gauge off.

The Elcometer 214L infrared thermometer with laser pointer is compact, lightweight and easy to use. Simply aim, pull the trigger and display the surface temperature of the object being measured. Release the trigger to hold the reading. Instant temperature readings and non-contact.

elcometer

ENGLAND

Elcometer Instruments Ltd Edge Lane Manchester M43 6BU

Tel: +44 (0) 161 371 6000 Fax: +44 (0) 161 371 6010 e-mail: sales@elcometer.com www.elcometer.com

USA

Elcometer Instruments Inc 1893 Rochester Industrial Drive Rochester Hills Michigan 48309

Tel: +1 248 650 0500 Toll free: 800 521 0635 Fax: +1 248 650 0501 e-mail: inc@elcometer.com www.elcometer.com

CANADA

Elcometer Canada Ltd PO Box 622, 401 Ouelette Avenue Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500 Toll Free: 800 521 0635 Fax: +1 248 650 0501 e-mail: ca_info@elcometer.com www.elcometer.com

ASIA & THE FAR FAST

Elcometer (Asia) Pte Ltd 896 Dunearn Rd Sime Darby Centre #3-09 Singapore 589472, Republic of Singapore

Tel: +65 6462 2822 Fax: +65 6462 2860 e-mail: asia@elcometer.com www.elcometer.com

BELGIUM

Elcometer SPRL Rue Vallée 13 B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10 Fax: +32 (0)4 374 06 03 e-mail: be_info@elcometer.be www.elcometer.be

FRANCE

Elcometer SARL BP 8-Bou 60 Rue de la Petite Levée 45430 Chécy

Tel: +33 (0)2 38 86 33 44 Fax: +33 (0)2 38 91 37 66 e-mail: fr_info@elcometer.fr www.elcometer.fr

GERMANY

Elcometer Instruments GmbH Himmlingstraβe 18 D-73434 Aalen

Tel: +49 (0) 7366 91 92 83 Fax: +49 (0) 7366 91 92 86 e-mail: de_info@elcometer.de www.elcometer.de